

## MODEL E386

Multi-chambered cleaner/rinser/dryer





P.O. Box 734 450 Taft Drive South Holland, IL 60473 800-276-2466 www.esmainc.com

# Features & Specs





Hot water input:

1/4"NPT, 1-GPM Max.

Rinse Output:

1/4"NPT (gravity feed)

Drain Ports Tanks 1 & 2:

1/4"NPT

\*High liquid level

protection built into

unit to prevent overflow.

Dimensions: 22"L x 13"W x 12"H

Tanks: 4.5 Quarts, 9.5"L x 5.5"W x 6"H

Ultrasonic power: 200/100 watts per tank

Power Requirements: 120V 60Hz 15A Hot Air Dryer: 1500 Watt

- All Stainless Steel Construction
- One year unconditional guarantee
   Two years on Power Circuit Boards
   Lifetime on Transducer Bonds and Weld Seams

### **APPLICATIONS**

- Springs
- Precision machining
- Medical Devices Drawn wire dies
- Clean Room applications
- Gears, filters
   Screw machine parts
- Housings, fittings
- Optics
- Cutting tools
- Many other cleaning applications

### **REMOVES (CLEANS)**

- Grinding residues
- Lapping Compounds
- Oils, lubricants
- Cutting compounds
- Buffing-polishing compounds
- Shop dirt
- Abrasives and waxes
- Loose burrs
- Particulars

#### RESULTS

- Bright parts (original surface re-stored)
- Easy inspection of internal bores.
- Easy overall inspection
- PERFECT CLEANING JOB
- No shadows in internal bores
- No debris in blind hole cavities
- Meets strict cleanup require-ments: no particles, no oils, bright, dry parts
- ✓ UNPRECEDENTED WARRANTY
- ✓ SINGLE PUSH-BUTTON ACTIVATION
- ✓ OVER 30 YEARS OF SUCCESSFUL IN-FIELD HISTORY
- ✓ ALL STAINLESS STEEL CONSTRUCTION